

NEW
“NAUTALIFT™ STAINLESS STEEL GAS LIFT SUPPORTS”
NEW

Marine Grade Gas Filled Supports –
Designed for demanding saltwater applications
316L Stainless Steel Rod and Cylinder
Engineered polymer rod ends
Bronze bushings
Multi-lobe internal seal



Part No.	OE No.	Extended Length (inches)	Compressed Length (inches)	Rated (pounds)
GSS62600	GSSX-4900-20	7.5	5.5	20
GSS62610	GSSX-4900-40	7.5	5.5	40
GSS62630	GSSX-5000-20	10	7	20
GSS62640	GSSX-5000-40	10	7	40
GSS62670	GSSX-5100-30	12	8.5	30
GSS62680	GSSX-5150-20	15	9.5	20
GSS62700	GSSX-5150-40	15	9.5	40
GSS62710	GSSX-5150-60	15	9.5	60
GSS62720	GSSX-5200-20	17	11	20
GSS62740	GSSX-5200-40	17	11	40
GSS62750	GSSX-5200-50	17	11	60
GSS62760	GSSX-5200-90	17	11	90
GSS62770	GSSX-5300-20	20	12	20
GSS62780	GSSX-5300-30	20	12	30
GSS62790	GSSX-5300-40	20	12	40
GSS62800	GSSX-5300-60	20	12	60
GSS62820	GSSX-2300-90	20	12	90
GSS62830	GSSX-2300-120	20	12	120



GS62840
Black zinc plated steel flat bracket with 10mm ball stud. 2.25" wide.



GS62850
Stainless steel flat bracket with 10mm ball stud. 2.25" wide.



GS62860
Black zinc plated steel 90° angle bracket with 10mm ball stud. 2" wide, .65" base.



GS62870
Stainless steel 90° angle bracket with 10mm ball stud. 2" wide, .65" base.



GS62880
Black zinc plated steel 90° angle bracket with 10mm ball stud. 2" x 1.2" base.



GS62900
Stainless steel 90° angle bracket with 10mm ball stud. 2" x 1.2" base.



GS62910
Zinc plated steel 10mm ball stud with threaded shaft.



GS62920
Stainless steel 10mm ball stud with threaded shaft.



GS62890
Rod end with internal threads for either end of Nautalift gas filled lift supports. Unique construction makes installation easy and safe.

ELEG. PROD.